


ES05Z1-K & H07Z1-K (AS)

ES05Z1-K (AS) (up to 1 mm²): 300/500 V. H07Z1-K (AS) (from 1,5 mm²): 450/750 V.

ES05Z1-K & H07Z1-K (AS)

USES

High security cable. It does not emit toxic substances in case of fire, therefore protecting people. It does not emit corrosive gases either, therefore preventing possible damage to electronic equipment. This is why its use is recommended for domestic installations and required in public places such as: shops, waiting rooms, offices, etc.




CHARACTERISTICS



USES



CERTIFICATIONS



B_{ca} s1a, d1,

DESING

[1] CONDUCTOR Electrolytic copper, class 5 (flexible) according to EN 60228.

[2] INSULATION Flame-resistant polyolefin, halogen-free and with low fume and corrosive gas emission in case of fire. Extra-slippery. Blue, black, brown, gray, or yellow/green colours.

CROSS SECTION [mm ²]	DIAMETER [mm]	WEIGHT [kg/km]	CABLE		INTENSITY (A)
			2 conductors at 30°C(A)	3 conductors at 30°C(A)	
1x1,5	2,9	19	17,5	15,5	31,9
1x2,5	3,6	30,0	24,0	21,0	19,2
1x4	4,1	44,0	32,0	28,0	11,9
1x6	4,6	61,0	41,0	36,0	7,92
1x10	5,9	104,0	57,0	50,0	4,58

Reference regulations

























HD 21.15 - UNE 211002

UNE-EN 60332-1 / UNE-EN 50266 /
UNE-EN 50267-1 / UNE-EN 50267-2 /
UNE-EN 61034

IEC 60332-1 / IEC 60332-3 / IEC
60754-1 / IEC 60754-2 / IEC 61034

ITC-BT: 9/15/20/26/28/29/30

>> BLISTER - SUPPLY CONDITIONS

SECTION [mm ²]	INSULATION COLOUR	Type	Capacity (m)	CODE	EAN CODE	MINIMUM ORDER	PRICE RATE
1x1,5		BOX	100	151V001MC100	8428722198980	5	
1x1,5		BOX	100	151A001MC100	8428722198966	5	
1x1,5		BOX	100	151M001MC100	8428722198973	5	
1x1,5		BOX	100	151N001MC100	8428722198997	5	
1x2,5		BOX	100	151V002MC100	8428722058888	5	
1x2,5		BOX	100	151A002MC100	8428722058543	5	
1x2,5		BOX	100	151M002MC100	8428722058680	5	
1x2,5		BOX	100	151N002MC100	8428722058765	5	
3x1x1,5		A	10	1503001MTWRBR10	8428722216509	10	
3x1x1,5		B	25	1503001MTWRBR25	8428722216493		
3x1x1,5		A	10	1503002MTWRBR10	8428722216516	8	
3x1x1,5		B	25	1503002MTWRBR25	8428722216523		
1x4		REEL	200	151V004.BP200	8428722215755		
1x4		REEL	200	151A004.BP200	8428722215762		
1x4		REEL	200	151M004.BP200	8428722215779		
1x4		REEL	200	151N004.BP200	8428722215786		
1x6		REEL	150	151V006.BP150	8428722215793		
1x6		REEL	150	151A006.BP150	8428722215809		
1x6		REEL	150	151M006.BP150	8428722215816		
1x6		REEL	150	151N006.BP150	8428722215823		
1x10		REEL	100	151V010.BP100	8428722215861		
1x10		REEL	100	151A010.BP100	8428722215847		
1x10		REEL	100	151M010.BP100	8428722215854		
1x10		REEL	100	151N010.BP100	8428722215830		

