


PVC CABLE

H03VVH2-F: 300/300 V. H05VVH2-F: 300/500 V.

H03VV-F H05VV-F

USES


Cable for powering electrical appliances in homes and offices. Small mechanical loads for the H03VV-F cable, such as radios, table lamps, hanging lamps, and office equipment. Medium mechanical loads for the H05VV-F cable, such as washing machines and refrigerators.



CHARACTERISTICS



USES



CERTIFICATIONS



DESIGN

[1] CONDUCTOR	Electrolytic copper, class 5 according to EN 60228.
[2] INSULATION	PVC.
[3] SHEATH	Flexible PVC, black or white colours.

TECHNICAL DATA

	CROSS SECTION [mm ²]	SHEATH/INSULATION COLOUR	DIAMETER [mm]	WEIGHT [kg/km]	INTENSITY (A)	CABLE
H03	3G0,75	○ / ●●●	5,8	53,9	3	H03VV-F
	2x1	○ / ●●	6,6	62,8	10	H05VV-F
H05VV-F	2x1	○ / ●●	6,6	62,8	10	H05VV-F
	2x1,5	● / ●●	7,4	83,6	16	H05VV-F
	2x1,5	○ / ●●	7,4	83,6	16	H05VV-F
	3G1	○ / ●●●	7,1	75,9	10	H05VV-F
	3G1	● / ●●●	7,1	75,9	10	H05VV-F
	3G1,5	○ / ●●●	8,2	105,1	16	H05VV-F
	3G1,5	● / ●●●	8,2	105,1	16	H05VV-F
	3G2,5	○ / ●●●	9,6	156,4	20	H05VV-F
	3G2,5	● / ●●●	9,6	156,4	20	H05VV-F

Reference regulations

UNE-21031-5

ITC-BT: 20/27/30/33/34/43/49

>> SUPPLY CONDITIONS

SECTION [mm ²]	SHEATH/INSULATION COLOUR	Type	Capacity (m)	CODE	EAN CODE	MINIMUM ORDER	PRICE RATE
3G0,75	○	A	5	0903000S03RBR05	8428722205893	14	
3G0,75	○	A	10	0903000S03RBR10	8428722205909	10	
2x1	○	A	5	0902001.RBR005	8428722205480	14	
2x1	○	A	10	0902001.RBR010	8428722205497	10	
2x1	●	A	10	1002001.RBR010	8428722205527	10	
2x1	●	B	25	1002001.RBR025	8428722205510	1	
2x1,5	○	A	5	0902001MRBR005	8428722199833	20	
2x1,5	○	A	10	0902001MRBR010	8428722199840	10	
2x1,5	○	B	25	0902001MRBR025	8428722205534	1	
2x1,5	●	A	10	1002001MRBR010	8428722200010	10	
2x1,5	●	B	25	1002001MRBR025	8428722205541	1	
3G1	○	A	5	0903001.RBR005	8428722202694	20	
3G1	○	A	10	0903001.RBR010	8428722200072	10	
3G1	○	B	25	0903001.RBR025	8428722205558	1	
3G1,5	○	A	5	0903001MRBR005	8428722200119	10	
3G1,5	○	A	10	0903001MRBR010	8428722200126	7	
3G1,5	○	B	25	0903001MRBR025	8428722205589	1	
3G1,5	○	B	50	0903001MRB50	8428722206371	1	
3G2,5	○	A	5	0903002MRBR005	8428722200188	8	
3G2,5	○	A	10	0903002MRBR010	8428722200195	7	
3G2,5	○	B	25	0903002MRBR025	8428722205619	1	
3G2,5	○	B	50	0903002MRB50	8428722206388	1	
2x1	○	REELS	200	0902001.BP200	8428722215571		
2x1	●	REELS	200	1002001.BP200	8428722215588		
2x1,5	○	REELS	200	0902001MBP200	8428722215625		
2x1,5	●	REELS	200	1002001MBP200	8428722215595		
3G1,5	○	REELS	200	0903001MBP200	8428722215632		
3G1,5	●	REELS	200	0903001MBP200	8428722215601		
3G2,5	○	REELS	150	0903002MBP150	8428722215649		
3G2,5	●	REELS	150	1003002MBP150	8428722215618		

TRANSPARENT HIGH TEMPERATURE CABLE

>> BLISTER - CONDITIONS OF SUPPLY

SECTION [mm ²]	SEATH/INSULATION COLOR	Type	Capacity (m)	CODE	EAN CODE	MINIMUM ORDER	PRICE RATE
2x0,75	TRANSPARENT	A	5	99003137RBR005	8428722216646	10	
2x0,75	TRANSPARENT	COILS	300	99003137BP300	8428722204278		

